

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number  
**WO 2005/040746 A3**

(51) International Patent Classification<sup>7</sup>: **G01L 5/04**, 1/10

(21) International Application Number:

PCT/GB2004/004308

(22) International Filing Date: 11 October 2004 (11.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

0323906.8 11 October 2003 (11.10.2003) GB

(71) Applicant (for all designated States except US): **THE UNIVERSITY OF LEEDS** [GB/GB]; Leeds LS2 9JT (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BANDARA, Palitha** [GB/GB]; The School of Textiles and Design, University of Leeds, Leeds LS2 9JT (GB).

(74) Agent: **HARRISON GODDARD FOOTE**; 31 St. Saviourgate, York YO1 8NQ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: TENSION MEASUREMENT BY OPTICAL MEANS



(57) Abstract: An apparatus and method for determining a tension in a target strand (11), e.g. a yarn is disclosed. The method and apparatus provides a non-contact way for determining tension in any type of elongate element simply and efficiently by means of an optical sensing head (14), e.g. of the CD linear array type.



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**(88) Date of publication of the international search report:**  
15 September 2005